



Close Window

Toolkit: Roll over to
Feedback | Help

Cisco Feature Navigator

Search by Feature

Search by Software

Compare Images

Objective: Define a specific software image in order to view its supported features.

Select from the pull down menus to find releases which support particular platform and feature set combinations. View your results in the table below and repeat as necessary to define a specific software image.

Your Selections:

Software	IOS
Major Release	12.2T
Release	12.2(4)T3
Platform	1720
Feature Set	IP/ADSL

[New Search](#)

Search Results

Image Info

Image Name	c1700-y7-mz.12.2-4.T3.bin
DRAM / Min Flash	32 / 8
Enterprise Product Number	S17C7-12204T S17C7-12204T=

[Compare Images](#) [View MIBs](#) [Release Notes](#) [Image Download Information](#)

Features

- [AAA Broadcast Accounting](#)
- [AAA DNIS Map for Authorization](#)
- [AAA Server Group](#)
- [AAA Server Group Deadtimer](#)
- [AAA Server Group Enhancements](#)
- [AAA Server Groups Based on DNIS](#)
- [ACL - Reflexive Access Lists](#)
- [Additional Vendor-Proprietary RADIUS Attributes](#)
- [Address Resolution Protocol \(ARP\)](#)
- [ADSL - Asymmetric Digital Subscriber Line Support](#)
- [Always On Dynamic ISDN \(AO/DI\)](#)
- [Asynchronous Rotary Line Queuing](#)
- [ATM PVC Trap Support](#)
- [ATM SNMP Trap and OAM Enhancements](#)
- [ATM-DXI](#)
- [AutoInstall over Frame Relay-ATM Interworking Connections](#)
- [AutoInstall Using DHCP for LAN Interfaces](#)
- [Automatic modem configuration](#)
- [Bandwidth Allocation Control Protocol \(BACP\)](#)
- [CDP \(Cisco Discovery Protocol\) Version 2](#)
- [Challenge Handshake Authentication Protocol \(CHAP\)](#)
- [Circuit Interface Identification Persistence for SNMP](#)
- [Class Based Weighted Fair Queuing \(CBWFQ\)](#)

[CLI String Search](#)
[CNS - Configuration Agent](#)
[CNS - Event Agent](#)
[Commented IP Access List Entries](#)
[Compression Control Protocol](#)
[CUG Selection Facility Suppress Option](#)
[Custom Queueing \(CQ\)](#)
[Customer Profile Idle Timer Enhancements for Interesting Traffic](#)
[Default Passive Interface](#)
[DHCP Client](#)
[DHCP Proxy Client](#)
[DHCP Relay Agent Support for Unnumbered Interfaces](#)
[DHCP Server](#)
[DHCP Server Options - Import and Autoconfiguration](#)
[Dial Backup](#)
[Dial-on-demand](#)
[Dialer Idle Timer Inbound Traffic Configuration](#)
[Dialer Persistent](#)
[Dialer Profiles](#)
[Dialer Watch](#)
[Diffserv Compliant WRED](#)
[DNS based X.25 routing](#)
[Double Authentication](#)
[Dynamic Multiple Encapsulation for Dial-in over ISDN](#)
[Easy IP \(Phase 1\)](#)
[EIGRP Stub Routing](#)
[Enhanced ATM VC Configuration and Management](#)
[Enhanced IGRP \(EIGRP\)](#)
[Enhanced Local Management Interface \(ELMI\)](#)
[Fast-Switched Policy Routing](#)
[Flow-Based WRED](#)
[Frame Relay](#)
[Frame Relay Encapsulation](#)
[Frame Relay End-to-End Keepalive](#)
[Frame Relay PVC Interface Priority Queueing](#)
[Frame Relay Router ForeSight](#)
[Frame Relay Switching](#)
[Frame Relay Traffic Shaping \(FRTS\)](#)
[FTP Support for Downloading Software Images](#)
[Generic Routing Encapsulation \(GRE\)](#)
[Generic Traffic Shaping \(GTS\)](#)
[Half bridge/half router for CPP and PPP](#)
[HSRP - Hot Standby Router Protocol](#)
[HSRP support for ICMP Redirects](#)
[HTTP Security](#)
[IGRP](#)
[Integrated routing and bridging \(IRB\)](#)
[Interface Alias Long Name Support](#)

[Interface Index Display](#)
[Interface Range Specification](#)
[Internet Protocol Control Protocol \(IPCP\) address negotiation](#)
[IP Enhanced IGRP Route Authentication](#)
[IP Header Compression Enhancement - PPPoATM and PPPoFR Support](#)
[IP Named Access Control List](#)
[IP Precedence for GRE Tunnels](#)
[IP Routing](#)
[IP SLAs - DHCP Operation](#)
[IP SLAs - Distribution of Statistics](#)
[IP SLAs - DSLW+ Operation](#)
[IP SLAs - DNS Operation](#)
[IP SLAs - FTP Operation](#)
[IP SLAs - HTTP Operation](#)
[IP SLAs - One Way Measurement](#)
[IP SLAs - Reaction Threshold](#)
[IP SLAs - Scheduler](#)
[IP SLAs - SNMP Support](#)
[IP SLAs - TCP Connect Operation](#)
[IP SLAs - UDP Jitter Operation](#)
[IP Summary Address for RIPv2](#)
[ISDN](#)
[ISDN Advice of Charge \(AOC\)](#)
[ISDN Caller ID Callback](#)
[ISDN Cause Code Override](#)
[ISDN Leased Line at 128kbps](#)
[Lock and Key](#)
[Low Latency Queueing \(LLQ\)](#)
[Low Latency Queueing \(LLQ\) for Frame Relay](#)
[Low Latency Queueing \(LLQ\) with Priority Percentage Support](#)
[MD5 File Validation](#)
[Message Banners for AAA Authentication](#)
[Microsoft Point-to-Point Compression \(MPPC\)](#)
[MLPPP - Multilink PPP](#)
[Modem User Interface Option](#)
[Modular QoS CLI \(MQC\)](#)
[MS Callback](#)
[MS-CHAP Version 1](#)
[Named Method Lists for AAA Authorization and Accounting](#)
[NAT - Network Address Translation](#)
[NAT - Support for NetMeeting Directory \(Internet Locator Service - ILS\)](#)
[NAT-Support of IP Phone to Cisco Call Manager](#)
[Next Hop Resolution Protocol \(NHRP\)](#)
[On Demand Routing \(ODR\)](#)
[OSPF](#)
[OSPF ABR type 3 LSA Filtering](#)
[OSPF Flooding Reduction](#)
[OSPF Not-So-Stubby Areas \(NSSA\)](#)

[OSPF On Demand Circuit \(RFC 1793\)](#)
[OSPF Packet Pacing](#)
[OSPF Stub Router Advertisement](#)
[PAD Subaddressing](#)
[Parse Bookmarks](#)
[Parser Cache](#)
[Password Authentication Protocol \(PAP\)](#)
[Per-User Configuration](#)
[Policy-Based Routing \(PBR\)](#)
[PPP](#)
[PPP over ATM](#)
[PPP over ATM \(IETF-Compliant\)](#)
[PPP over Frame Relay](#)
[Priority Queueing \(PQ\)](#)
[QoS Priority Percentage CLI Support](#)
[RADIUS](#)
[RADIUS Attribute 44 \(Accounting Session ID\) in Access Requests](#)
[RADIUS for Multiple User Datagram Protocol Ports](#)
[Response Time Reporter \(RTR\)](#)
[Response Time Reporter \(RTR\) enhancements](#)
[Restart-delay Granularity](#)
[RIP](#)
[RMON events and alarms](#)
[Selective Packet Discard \(SPD\)](#)
[Simple Network Time Protocol \(SNTP\)](#)
[Snapshot routing](#)
[SNMP \(Simple Network Management Protocol\)](#)
[SNMP Support over VPN](#)
[SNMPv2C](#)
[SNMPv3 \(SNMP Version 3\)](#)
[Spanning Tree Protocol \(STP\)](#)
[Spanning Tree Protocol \(STP\) Extension](#)
[Standard IP Access List Logging](#)
[Switched Multimegabit Data Service \(SMDS\)](#)
[Tacacs SENDAUTH function](#)
[Tacacs Single Connection](#)
[TACACS+](#)
[Time-Based Access Lists Using Time Ranges](#)
[Transparent Bridging](#)
[Triggered RIP](#)
[User Maximum Links](#)
[Virtual Interface Template Service](#)
[Virtual Profiles](#)
[Weighted Fair Queueing \(WFQ\)](#)
[Weighted RED \(WRED\)](#)
[x Digital Subscriber Line \(xDSL\) Bridge Support](#)
[X.25](#)
[X.25 Closed User Group](#)

[X.25 Failover](#)

[X.25 Load Balancing](#)

[X.25 on ISDN D-Channel](#)

[X.25 over Frame Relay \(Annex G\)](#)

[X.25 over TCP \(XOT\)](#)

[X.25 Remote Failure Detection](#)

[X.25 Switch Local Acknowledgement](#)

[X.25 Switching between PVCs and SVCs](#)

[X.28 Emulation](#)

Some features are dependent on product model, interface modules (i.e. Line Cards & Port Adapters), and/or require a software feature license. [Click](#) here for more information.

Close Window

© 1992-2006 Cisco Systems, Inc. All rights reserved.

[Terms & Conditions](#) | [Privacy Statement](#) | [Cookie Policy](#) | [Trademarks of Cisco Systems, Inc.](#)