



Close Window

Toolkit: Roll over to

Feedback | Help

Cisco Feature Navigator

Search by Feature

Search by Software

Compare Images

Objective: Define a specific software image in order to view its supported features.

Select from the pull down menus to find releases which support particular platform and feature set combinations. View your results in the table below and repeat as necessary to define a specific software image.

Your Selections:

Software **IOS**

Major Release **12.2**

Release

[Platform](#)

Feature Set

[New Search](#)

Search Results

Image Info

Image Name	c2500-ik8s-l.12.2-19a.bin
DRAM / Min Flash	10 / 16
Enterprise Product Number	S25CK8-12219 S25CK8-12219=

[Compare Images](#)
[View MIBs](#)
[Release Notes](#)
[Image Download Information](#)

Features

- [AAA Broadcast Accounting](#)
- [AAA DNIS Map for Authorization](#)
- [AAA Server Group](#)
- [AAA Server Group Deadtimer](#)
- [AAA Server Group Enhancements](#)
- [AAA Server Groups Based on DNIS](#)
- [ACL - Reflexive Access Lists](#)
- [Additional Vendor-Proprietary RADIUS Attributes](#)
- [Address Resolution Protocol \(ARP\)](#)
- [Airline Product Set \(ALPS\)](#)
- [Airline Product Set Enhancements \(MATIP\)](#)
- [Always On Dynamic ISDN \(AO/DI\)](#)
- [Asynchronous Serial Traffic Over UDP](#)
- [ATM-DXI](#)
- [AutoInstall Using DHCP for LAN Interfaces](#)
- [Automatic modem configuration](#)
- [Bandwidth Allocation Control Protocol \(BACP\)](#)
- [BGP](#)
- [BGP 4](#)
- [BGP 4 Multipath Support](#)
- [BGP 4 Prefix Filter and In-bound Route Maps](#)
- [BGP 4 Soft Config](#)
- [BGP Soft Reset](#)

[Bidirectional PIM](#)
[Bisync \(BSC\)](#)
[BSTUN \(Block Serial Tunneling\)](#)
[CDP \(Cisco Discovery Protocol\) Version 2](#)
[CEF/dCEF - Cisco Express Forwarding](#)
[Certification Authority Interoperability \(CA\)](#)
[CGMP - Cisco Group Management Protocol](#)
[Challenge Handshake Authentication Protocol \(CHAP\)](#)
[Class Based Weighted Fair Queuing \(CBWFQ\)](#)
[Class-Based Shaping](#)
[CLI String Search](#)
[CNS - Client](#)
[Combinet Packet Protocol \(CPP\)](#)
[Commented IP Access List Entries](#)
[Committed Access Rate \(CAR\)](#)
[Compression Control Protocol](#)
[CUG Selection Facility Suppress Option](#)
[Custom Queueing \(CQ\)](#)
[Default Passive Interface](#)
[DHCP Client](#)
[DHCP Proxy Client](#)
[DHCP Relay Agent Support for Unnumbered Interfaces](#)
[DHCP Server](#)
[DHCP Server Options - Import and Autoconfiguration](#)
[Dial Backup](#)
[Dial on Demand Authentication Enhancements](#)
[Dial-on-demand](#)
[Dialer Idle Timer Inbound Traffic Configuration](#)
[Dialer Profiles](#)
[Dialer Watch](#)
[Diffie-Hellman Group 5](#)
[DLSw \(RFC 1795\)](#)
[DLSw CO features](#)
[DLSw V2](#)
[DLSw+](#)
[DLSw+ Asynchronous TCP Enhancements](#)
[DLSw+ Backup Peer Extensions for Encapsulation Types](#)
[DLSw+ Border Peer Caching](#)
[DLSw+ Enhanced Load Balancing](#)
[DLSw+ Ethernet Redundancy](#)
[DLSw+ Peer Group Clusters](#)
[DLSw+ RSVP Bandwidth Reservation](#)
[DLSw+ SNA Type of Service](#)
[DLSw+ Support For Transporting LLC1 UI Traffic](#)
[DNS based X.25 routing](#)
[Double Authentication](#)
[Down Stream Physical Unit \(DSPU\) over DLSw+](#)
[Downstream PU concentration \(DSPU\)](#)

[DRP Server Agent](#)
[Dynamic Multiple Encapsulation for Dial-in over ISDN](#)
[Easy IP \(Phase 1\)](#)
[EGP](#)
[EIGRP Stub Routing](#)
[Enhanced ATM VC Configuration and Management](#)
[Enhanced IGRP \(EIGRP\)](#)
[Enhanced Local Management Interface \(ELMI\)](#)
[Express RTP and TCP Header Compression](#)
[Fast-Switched Policy Routing](#)
[Fast-Switched SRTLB](#)
[Flow-Based WRED](#)
[Frame Relay](#)
[Frame Relay Access Support \(FRAS\) Border Access Node \(BAN\)](#)
[Frame Relay Access Support \(FRAS\) Boundary Network Node \(BNN\)](#)
[Frame Relay Access Support \(FRAS\) Dial Backup over DSLW+](#)
[Frame Relay Access Support \(FRAS\) DLCI Backup](#)
[Frame Relay Access Support \(FRAS\) Host](#)
[Frame Relay ELMI Address Registration](#)
[Frame Relay Encapsulation](#)
[Frame Relay End-to-End Keepalive](#)
[Frame Relay Fragmentation \(FRF.12\)](#)
[Frame Relay FRF.9 Payload Compression](#)
[Frame Relay PVC Interface Priority Queueing](#)
[Frame Relay Router ForeSight](#)
[Frame Relay Switching](#)
[Frame Relay Switching Diagnostics and Troubleshooting](#)
[Frame Relay Switching Enhancements: Shaping and Policing](#)
[Frame Relay Traffic Shaping \(FRTS\)](#)
[Frame Relay Tunnel Switching](#)
[FTP Support for Downloading Software Images](#)
[Generated SysObjectIDs](#)
[Generic Routing Encapsulation \(GRE\)](#)
[Generic Traffic Shaping \(GTS\)](#)
[Half bridge/half router for CPP and PPP](#)
[HSRP - Hot Standby Router Protocol](#)
[HSRP support for ICMP Redirects](#)
[HTTP Security](#)
[IGMP Version 1](#)
[IGMP Version 3](#)
[IGRP](#)
[IKE Extended Authentication \(Xauth\)](#)
[IKE Mode Configuration](#)
[IKE Security Protocol](#)
[IKE Shared Secret Using AAA Server](#)
[Integrated routing and bridging \(IRB\)](#)
[Interface Index Persistence](#)
[Interface Range Specification](#)

[Internet Protocol Control Protocol \(IPCP\) address negotiation](#)

[IP Enhanced IGRP Route Authentication](#)

[IP Multicast Load Splitting across Equal-Cost Paths](#)

[IP Named Access Control List](#)

[IP Precedence for GRE Tunnels](#)

[IP Routing](#)

[IP RTP Priority](#)

[IP SLAs - DHCP Operation](#)

[IP SLAs - Distribution of Statistics](#)

[IP SLAs - DLSW+ Operation](#)

[IP SLAs - DNS Operation](#)

[IP SLAs - FTP Operation](#)

[IP SLAs - HTTP Operation](#)

[IP SLAs - One Way Measurement](#)

[IP SLAs - Reaction Threshold](#)

[IP SLAs - Scheduler](#)

[IP SLAs - SNMP Support](#)

[IP SLAs - TCP Connect Operation](#)

[IP SLAs - UDP Jitter Operation](#)

[IP Summary Address for RIPv2](#)

[IPSec Network Security](#)

[ISDN](#)

[ISDN Advice of Charge \(AOC\)](#)

[ISDN Caller ID Callback](#)

[ISDN Cause Code Override](#)

[L2TP Dial-Out](#)

[L2TP Layer 2 Tunneling Protocol](#)

[L2TP Tunnel Preservation of IP TOS](#)

[LAN Network Manager over DLSw+](#)

[Large Scale Dialout \(LSDO\)](#)

[Layer 2 Forwarding-Fast Switching](#)

[Line Printer Daemon \(LPD\)](#)

[Lock and Key](#)

[Low Latency Queueing \(LLQ\)](#)

[Low Latency Queueing \(LLQ\) for Frame Relay](#)

[Message Banners for AAA Authentication](#)

[Microsoft Point-to-Point Compression \(MPPC\)](#)

[MLPPP - Multilink PPP](#)

[Mobile IP](#)

[Mobile IP Home Agent \(HA\) Redundancy](#)

[Modular QoS CLI \(MQC\)](#)

[MS Callback](#)

[MS-CHAP Version 1](#)

[Multicast BGP \(MBGP\)](#)

[Multicast NAT](#)

[Multicast Routing Monitor \(MRM\)](#)

[Multicast Source Discovery Protocol \(MSDP\)](#)

[Multichassis MultiLink PPP \(MMP\)](#)

[Multihop VPDN](#)
[Named Method Lists for AAA Authorization and Accounting](#)
[NAT - Network Address Translation](#)
[NAT - Support for NetMeeting Directory \(Internet Locator Service - ILS\)](#)
[NAT-Support of IP Phone to Cisco Call Manager](#)
[National ISDN Switch Types for BRI and PRI Interfaces](#)
[Native Client Interface Architecture \(NCIA\) Server](#)
[Native Service Point over DLSW+](#)
[NetFlow](#)
[Network Time Protocol \(NTP\)](#)
[Next Hop Resolution Protocol \(NHRP\)](#)
[On Demand Routing \(ODR\)](#)
[OSPF](#)
[OSPF Flooding Reduction](#)
[OSPF Not-So-Stubby Areas \(NSSA\)](#)
[OSPF On Demand Circuit \(RFC 1793\)](#)
[OSPF Packet Pacing](#)
[PAD Subaddressing](#)
[Parse Bookmarks](#)
[Parser Cache](#)
[Password Authentication Protocol \(PAP\)](#)
[Per-User Configuration](#)
[PIM Dense Mode State Refresh](#)
[PIM Version 1](#)
[PIM Version 2](#)
[Policy-Based Routing \(PBR\)](#)
[PPP](#)
[PPP over Frame Relay](#)
[PPTP with MPPE](#)
[Priority Queueing \(PQ\)](#)
[Qualified Logical Link Control \(QLLC\)](#)
[RADIUS](#)
[RADIUS Attribute 44 \(Accounting Session ID\) in Access Requests](#)
[RADIUS for Multiple User Datagram Protocol Ports](#)
[Random Early Detection \(RED\)](#)
[Remote Source-Route Bridging \(RSRB\)](#)
[Response Time Reporter \(RTR\)](#)
[Response Time Reporter \(RTR\) enhancements](#)
[RGMP - Router-Port Group Management Protocol](#)
[RIF Passthru in DLSw+](#)
[RIP](#)
[RMON events and alarms](#)
[RMON full](#)
[RSVP - Resource Reservation Protocol](#)
[RTP Header Compression](#)
[SDLC SNRM Timer and Window Size Enhancements](#)
[SDLC-to-LAN conversion \(SDLLC\)](#)
[Secure Shell SSH Version 1 Integrated Client](#)

[Secure Shell SSH Version 1 Server Support](#)

[Selective Packet Discard \(SPD\)](#)

[Selective Virtual-Access Interface Creation](#)

[Single Rate 3-Color Marker for Traffic Policing](#)

[Snapshot routing](#)

[SNMP \(Simple Network Management Protocol\)](#)

[SNMP Manager](#)

[SNMPv2C](#)

[SNMPv3 \(SNMP Version 3\)](#)

[Source Specific Multicast \(SSM\)](#)

[Spanning Tree Protocol \(STP\)](#)

[Spanning Tree Protocol \(STP\) Extension](#)

[SRB - Source-Route bridging](#)

[SRB over Frame Relay](#)

[Stack Group Bidding Protocol \(SGBP\)](#)

[Standard IP Access List Logging](#)

[Stub IP Multicast Routing](#)

[STUN \(Serial Tunnel\)](#)

[Subnetwork Bandwidth Manager \(SBM\)](#)

[Switched Multimegabit Data Service \(SMDS\)](#)

[Synchronous Data Link Control \(SDLC\)](#)

[Tacacs SENDAUTH function](#)

[Tacacs Single Connection](#)

[TACACS+](#)

[Time-Based Access Lists Using Time Ranges](#)

[Transparent Bridging](#)

[Triggered RIP](#)

[Trusted Root Certification Authority](#)

[Tunnel Endpoint Discovery](#)

[Tunneling of Asynchronous Security Protocols](#)

[Uni-Directional Link Routing \(UDLR\)](#)

[Unicast Reverse Path Forwarding \(uRPF\)](#)

[User Maximum Links](#)

[Virtual Interface Template Service](#)

[Virtual Private Dial-up Network \(VPDN\)](#)

[Virtual Profiles](#)

[VPN Tunnel Management](#)

[WCCP Redirection on Inbound Interfaces](#)

[WCCP Version 1](#)

[WCCP Version 2](#)

[Weighted Fair Queueing \(WFQ\)](#)

[Weighted RED \(WRED\)](#)

[Wildcard Pre-Shared Key](#)

[X.25](#)

[X.25 Calling Address Insertion and Removal Based on Input Interface](#)

[X.25 Closed User Group](#)

[X.25 Failover](#)

[X.25 Load Balancing](#)

[X.25 on ISDN D-Channel](#)

[X.25 over Frame Relay \(Annex G\)](#)

[X.25 over TCP \(XOT\)](#)

[X.25 Remote Failure Detection](#)

[X.25 Switch Local Acknowledgement](#)

[X.25 Switching between PVCs and SVCs](#)

[X.28 Emulation](#)

Some features are dependent on product model, interface modules (i.e. Line Cards & Port Adapters), and/or require a software feature license. [Click](#) here for more information.

Close Window

© 1992-2006 Cisco Systems, Inc. All rights reserved.

[Terms & Conditions](#) | [Privacy Statement](#) | [Cookie Policy](#) | [Trademarks of Cisco Systems, Inc.](#)