



Cisco Feature Navigator

[Search by Feature](#)
[Search by Software](#)
[Compare Images](#)

Objective: Define a specific software image in order to view its supported features.

Select from the pull down menus to find releases which support particular platform and feature set combinations. View your results in the table below and repeat as necessary to define a specific software image.

Your Selections:

Software	IOS
Major Release	12.2T
Release	<input type="text" value="12.2(8)T5"/>
Platform	<input type="text" value="2610-2613"/>
Feature Set/License	<input type="text" value="IP"/>

[New Search](#)

Search Results

Image Info

Image Name	c2600-i-mz.122-8.T5.bin
DRAM / Min Flash	32 / 8
Enterprise Product Number	S26C-12208T S26C-12208T=

[Compare Images](#)
[View MIBs](#)
[Release Notes](#)
[Image Download Information](#)

Features

- [AAA Broadcast Accounting](#)
- [AAA DNIS Map for Authorization](#)
- [AAA Server Group](#)
- [AAA Server Group Deadtimer](#)
- [AAA Server Group Enhancements](#)
- [AAA Server Groups Based on DNIS](#)
- [ACL - Reflexive Access Lists](#)
- [ACL Authentication of Incoming RSH and RCP](#)
- [Adaptive Frame Relay Traffic Shaping for Interface Congestion](#)
- [Additional Vendor-Proprietary RADIUS Attributes](#)
- [Address Resolution Protocol \(ARP\)](#)
- [Always On Dynamic ISDN \(AO/DI\)](#)
- [Asynchronous Line Monitoring](#)

[Asynchronous Rotary Line Queuing](#)
[Asynchronous Serial Traffic Over UDP \(aka UDPTN\)](#)
[ATM Cell Loss Priority \(CLP\) Setting](#)
[ATM-DXI](#)
[AutoInstall Using DHCP for LAN Interfaces](#)
[Automatic modem configuration](#)
[Bandwidth Allocation Control Protocol \(BACP\)](#)
[BGP](#)
[BGP 4](#)
[BGP 4 Multipath Support](#)
[BGP 4 Prefix Filter and In-bound Route Maps](#)
[BGP 4 Soft Config](#)
[BGP Conditional Route Injection](#)
[BGP Hide Local-Autonomous System](#)
[BGP Link Bandwidth](#)
[BGP Named Community Lists](#)
[BGP Prefix-Based Outbound Route Filtering](#)
[BGP Soft Reset](#)
[Bidirectional PIM](#)
[CDP \(Cisco Discovery Protocol\) Version 2](#)
[CEF on Multipoint GRE Tunnels](#)
[CEF/dCEF - Cisco Express Forwarding](#)
[CGMP - Cisco Group Management Protocol](#)
[Challenge Handshake Authentication Protocol \(CHAP\)](#)
[Channelized E1 Signaling](#)
[Circuit Interface Identification Persistence for SNMP](#)
[Cisco Discovery Protocol \(CDP\) over ATM](#)
[Class Based Ethernet CoS Matching & Marking \(802.1p & ISL CoS\)](#)
[Class Based Weighted Fair Queuing \(CBWFQ\)](#)
[Class-Based Frame-Relay DE-Bit Matching and Marking](#)
[Class-Based Marking](#)
[Class-Based Policing](#)
[Class-Based Shaping](#)
[CLI String Search](#)
[ClickStart](#)
[CNS - Configuration Agent](#)
[CNS - Event Agent](#)
[CNS - Flow Through Provisioning](#)
[Commented IP Access List Entries](#)
[Committed Access Rate \(CAR\)](#)

[Compression Control Protocol](#)
[Configurable per ATM-VC Hold Queue size](#)
[Control Plane DSCP Support for RSVP](#)
[COPS for RSVP](#)
[CT1/RBS \(Robbed Bit Signaling\)](#)
[CUG Selection Facility Suppress Option](#)
[Custom Queueing \(CQ\)](#)
[Customer Profile Idle Timer Enhancements for Interesting Traffic](#)
[Default Passive Interface](#)
[DHCP Client](#)
[DHCP Client - Dynamic Subnet Allocation API](#)
[DHCP Client on WAN Interfaces](#)
[DHCP Proxy Client](#)
[DHCP Relay Agent Support for Unnumbered Interfaces](#)
[DHCP Server](#)
[DHCP Server Options - Import and Autoconfiguration](#)
[Dial Backup](#)
[Dial on Demand Authentication Enhancements](#)
[Dial-on-demand](#)
[Dialer CEF](#)
[Dialer Idle Timer Inbound Traffic Configuration](#)
[Dialer Persistent](#)
[Dialer Profiles](#)
[Dialer Watch](#)
[Dialer Watch Connect Delay](#)
[Diffserv Compliant WRED](#)
[Digital J1 Voice Support](#)
[DNS based X.25 routing](#)
[Double Authentication](#)
[DRP Server Agent](#)
[Dynamic Multiple Encapsulation for Dial-in over ISDN](#)
[E1 R2 Signaling](#)
[Easy IP \(Phase 1\)](#)
[EIGRP Stub Routing](#)
[Encrypted Vendor Specific Attributes](#)
[Enhanced IGRP \(EIGRP\)](#)
[Enhanced Local Management Interface \(ELMI\)](#)
[Enhanced Password Security](#)
[Express RTP and TCP Header Compression](#)
[Fast-Switched Policy Routing](#)

[Flow-Based WRED](#)

[Frame Relay](#)

[Frame Relay ELMI Address Registration](#)

[Frame Relay Encapsulation](#)

[Frame Relay End-to-End Keepalive](#)

[Frame Relay FRF.9 Payload Compression](#)

[Frame Relay PVC Interface Priority Queueing](#)

[Frame Relay Router ForeSight](#)

[Frame Relay Switching](#)

[Frame Relay Switching Diagnostics and Troubleshooting](#)

[Frame Relay Switching Enhancements: Shaping and Policing](#)

[Frame Relay Traffic Shaping \(FRTS\)](#)

[Frame Relay Tunnel Switching](#)

[FTP Support for Downloading Software Images](#)

[Generic Routing Encapsulation \(GRE\)](#)

[Generic Routing Encapsulation \(GRE\) Tunnel Keepalive](#)

[Generic Traffic Shaping \(GTS\)](#)

[Half bridge/half router for CPP and PPP](#)

[HSRP - Hot Standby Router Protocol](#)

[HSRP support for ICMP Redirects](#)

[HTTP Security](#)

[iBGP Multipath Load Sharing](#)

[IGMP Fast Leave](#)

[IGMP MIB Support Enhancements for SNMP](#)

[IGMP Version 3](#)

[IGMP Version 3 - Explicit Tracking of Hosts, Groups, and Channels](#)

[IGRP](#)

[Integrated routing and bridging \(IRB\)](#)

[Interface Alias Long Name Support](#)

[Interface Index Display](#)

[Interface Index Persistence](#)

[Interface Range Specification](#)

[Internet Protocol Control Protocol \(IPCP\) address negotiation](#)

[IP DSCP marking for Frame-Relay PVC](#)

[IP Enhanced IGRP Route Authentication](#)

[IP Multicast Load Splitting across Equal-Cost Paths](#)

[IP Named Access Control List](#)

[IP Precedence for GRE Tunnels](#)

[IP Routing](#)

[IP RTP Priority](#)

[IP SLAs - DHCP Operation](#)

[IP SLAs - Distribution of Statistics](#)

[IP SLAs - DLSW+ Operation](#)

[IP SLAs - DNS Operation](#)

[IP SLAs - Frame Relay Operation](#)

[IP SLAs - FTP Operation](#)

[IP SLAs - HTTP Operation](#)

[IP SLAs - One Way Measurement](#)

[IP SLAs - Path Jitter Operation](#)

[IP SLAs - Reaction Threshold](#)

[IP SLAs - Scheduler](#)

[IP SLAs - SNMP Support](#)

[IP SLAs - TCP Connect Operation](#)

[IP SLAs - UDP Jitter Operation](#)

[IP Summary Address for RIPv2](#)

[IP-to-ATM CoS](#)

[ISDN](#)

[ISDN Advice of Charge \(AOC\)](#)

[ISDN Caller ID Callback](#)

[ISDN Cause Code Override](#)

[ISDN Leased Line at 128kbps](#)

[ISDN Network Side for ETSI Net5 PRI](#)

[ISDN NFAS](#)

[Line Printer Daemon \(LPD\)](#)

[Link Fragmentation and Interleaving \(LFI\) for Frame Relay and ATM Virtual Circuits](#)

[Lock and Key](#)

[Low Latency Queueing \(LLQ\)](#)

[Low Latency Queueing \(LLQ\) for Frame Relay](#)

[Low Latency Queueing \(LLQ\) with Priority Percentage Support](#)

[LSDO: L2TP Large-Scale Dial-Out](#)

[MD5 File Validation](#)

[Message Banners for AAA Authentication](#)

[Microsoft Point-to-Point Compression \(MPPC\)](#)

[MLPPP - Multilink PPP](#)

[Modem Chat Script and System Script Support in LSDO](#)

[Modem over BRI](#)

[Modem User Interface Option](#)

[Modular QoS CLI \(MQC\)](#)

[MS Callback](#)

[MS-CHAP Version 1](#)

[Multicast BGP \(MBGP\)](#)

[Multicast NAT](#)

[Multicast Routing Monitor \(MRM\)](#)

[Multicast Source Discovery Protocol \(MSDP\)](#)

[Named Method Lists for AAA Authorization and Accounting](#)

[NAT - Ability to use Routes Maps with Static Translations](#)

[NAT - Network Address Translation](#)

[NAT - Static Mapping Support with HSRP for High-Availability](#)

[NAT - Support for NetMeeting Directory \(Internet Locator Service - ILS\)](#)

[NAT - Translation of external IP Addresses only](#)

[NAT-Support of IP Phone to Cisco Call Manager](#)

[National ISDN Switch Types for BRI and PRI Interfaces](#)

[NBAR - Network-based Application Recognition](#)

[NBAR Real-time Transport Protocol Payload Classification](#)

[NetFlow](#)

[NetFlow Aggregation](#)

[Netflow Multiple Export Destinations](#)

[NetFlow Policy Routing \(NPR\)](#)

[NetFlow ToS-Based Router Aggregation](#)

[Network Side ISDN PRI Signaling, Trunking, and Switching](#)

[Network Time Protocol \(NTP\)](#)

[Next Hop Resolution Protocol \(NHRP\)](#)

[On Demand Routing \(ODR\)](#)

[Optimized PPP Negotiation](#)

[OSPF](#)

[OSPF ABR type 3 LSA Filtering](#)

[OSPF Flooding Reduction](#)

[OSPF Not-So-Stubby Areas \(NSSA\)](#)

[OSPF On Demand Circuit \(RFC 1793\)](#)

[OSPF Packet Pacing](#)

[OSPF Sham-Link Support for MPLS VPN](#)

[OSPF Stub Router Advertisement](#)

[OSPF Update Packet-Pacing Configurable Timers](#)

[PAD Subaddressing](#)

[Parse Bookmarks](#)

[Parser Cache](#)

[Password Authentication Protocol \(PAP\)](#)

[Per-User Configuration](#)

[PIM Dense Mode State Refresh](#)

[PIM MIB Extension for IP Multicast](#)

[PIM Version 1](#)
[PIM Version 2](#)
[Policer Enhancement - Multiple Actions](#)
[Policy-Based Routing \(PBR\)](#)
[PPP](#)
[PPP over ATM](#)
[PPP over Frame Relay](#)
[Priority Queueing \(PQ\)](#)
[QoS Device Manager \(QDM\)](#)
[QoS for Virtual Private Networks](#)
[QoS Packet Marking](#)
[QoS Priority Percentage CLI Support](#)
[RADIUS](#)
[RADIUS Attribute 44 \(Accounting Session ID\) in Access Requests](#)
[RADIUS for Multiple User Datagram Protocol Ports](#)
[RADIUS Route Download](#)
[Random Early Detection \(RED\)](#)
[Redial Enhancements](#)
[Response Time Reporter \(RTR\)](#)
[Response Time Reporter \(RTR\) enhancements](#)
[Restart-delay Granularity](#)
[RGMP - Router-Port Group Management Protocol](#)
[RIP](#)
[RMON events and alarms](#)
[Rotating Through Dial Strings](#)
[RSVP - Resource Reservation Protocol](#)
[RSVP Scalability Enhancements](#)
[RSVP Support for Frame Relay](#)
[RSVP support for LLQ](#)
[RTP Header Compression](#)
[Selective Packet Discard \(SPD\)](#)
[Selective Virtual-Access Interface Creation](#)
[Single Rate 3-Color Marker for Traffic Policing](#)
[Snapshot routing](#)
[SNMP \(Simple Network Management Protocol\)](#)
[SNMP Support over VPN](#)
[SNMPv2C](#)
[SNMPv3 \(SNMP Version 3\)](#)
[Source Specific Multicast \(SSM\)](#)
[Source Specific Multicast \(SSM\) - IGMPv3, IGMP v3lite, and URD](#)

[Spanning Tree Protocol \(STP\)](#)
[Spanning Tree Protocol \(STP\) Extension](#)
[Standard IP Access List Logging](#)
[Stub IP Multicast Routing](#)
[Subnetwork Bandwidth Manager \(SBM\)](#)
[Switched Multimegabit Data Service \(SMDS\)](#)
[Tacacs SENDAUTH function](#)
[Tacacs Single Connection](#)
[TACACS+](#)
[TCP Window Scaling](#)
[Time-Based Access Lists Using Time Ranges](#)
[Transparent Bridging](#)
[Tunnel Type of Service \(TOS\)](#)
[Turbo Flooding of UDP Datagrams](#)
[Two-Rate Policer](#)
[UDLR Tunnel ARP and IGMP Proxy](#)
[Uni-Directional Link Routing \(UDLR\)](#)
[Unicast Reverse Path Forwarding \(uRPF\)](#)
[User Maximum Links](#)
[Using 31-bit Prefixes on IPv4 Point-to-Point Links](#)
[V.92 Modem on Hold](#)
[Vendor-Specific RADIUS Attributes](#)
[Virtual Interface Template Service](#)
[Virtual Profile CEF Switched](#)
[Virtual Profiles](#)
[WCCP Redirection on Inbound Interfaces](#)
[WCCP Version 1](#)
[WCCP Version 2](#)
[Weighted Fair Queueing \(WFQ\)](#)
[Weighted RED \(WRED\)](#)
[WRED Enhancement - Explicit Congestion Notification \(ECN\)](#)
[x Digital Subscriber Line \(xDSL\) Bridge Support](#)
[X.25](#)
[X.25 Annex G Session Status Change Reporting](#)
[X.25 Closed User Group](#)
[X.25 Load Balancing](#)
[X.25 on ISDN D-Channel](#)
[X.25 over Frame Relay \(Annex G\)](#)
[X.25 over TCP \(XOT\)](#)
[X.25 Over TCP Profiles](#)

[X.25 Remote Failure Detection](#)

[X.25 Switch Local Acknowledgement](#)

[X.25 Switching between PVCs and SVCs](#)

[X.28 Emulation](#)

Some features are dependent on product model, interface modules (i.e. Line Cards & Port Adapters), and/or require a software feature license. [Click](#) here for more information.

© 1992-2008 Cisco Systems, Inc. All rights reserved.

[Terms & Conditions](#) | [Privacy Statement](#) | [Cookie Policy](#) | [Trademarks of Cisco Systems, Inc.](#)